

UV MARKING INK

UV硬化型文字油墨

· 具有優良之網板印刷適性與清晰性	· Excellent screen printing property with high resolution
· 對於焊錫組裝，具優良之耐熱性及耐化性	· Offer good adhesion to solder mask, heat resistance and chemical resistance
· 對於溶劑與助焊劑，具優良之抵抗力	· Resistance to solvent and flux
· 油墨無臭味與皮膚腐蝕性	· Odorless and low irritating index

項目 / ITEM	ETERCURE 692 W	ETERCURE 692 Y	ETERCURE 692 B
色調 / Color	白色 / White	黃色 / Yellow	黑色 / Black
曝光能量 (能量盤 : ORC UV351) Exposure (detector : ORC UV351)	1200 ~ 1800 mJ/cm ²	1600 ~ 2200 mJ/cm ²	1800 ~ 2400 mJ/cm ²
比重 / Density	1.35 ~ 1.50		
閃火點 / Flash Point	> 100°C		
黏度 (VT-04F型、No.2、25°C) Viscosity (VT-04F type、No.2、25°C)	160 ~ 300 ps		
儲存期 (25°C以下之暗室) SHELF LIFE (in dark room below 25°C)	12個月 / 12 months after production		
塗膜硬度 / Hardness	≥ 3H		
密著性 / Adhesion	100/100		
耐焊錫性 (260°C/5secs) Solder Heat Resistance (260°C/5secs)	塗膜無剝離 / No ink peels off		
耐燃性 / Flammability	UL 94V-0		

